

Solar Energy Residential Battery Storage System Stacked With Lithium Ion Battery

UN38.3, MSDS, UL, CB, BIS, PSE, GB4943.1

Basic Information

- Place of Origin:
- Brand Name: XWELL
- Certification:
 - safety standard, CE, FCC, ROHS, battery UN38.3, MSDS, UL, CB, BIS, PSE
- Model Number: XW-HH1024
- Minimum Order Quantity: 1 pcs
- Packaging Details: Carton
- Delivery Time:
- Payment Terms: L/C, D/A, D/P, T/T, Western Union, MoneyGram

7-10 working days

5000 pcs per month

China

Supply Ability:



Product Specification

Modules:	4
 Capacity Full Charge: 	10.24kwh
 Cell Quantity: 	64S1P
 Voltage: 	182.4-230.4V
 Weight: 	115kg
 Nominal Voltage: 	153.6V
 Dimension: 	550x430x697.5mm
 Battery Cell Type: 	LiFePO4
 Rated Working Current: 	50A
Communication AC110V/220V/50Hz/60Hzr	CAN/RS485/RS232 nethod:
• Highlight:	Solar Residential Battery Storage Systen Residential Battery Storage System Stac Lithium Ion residential solar battery syst

Our Product Introduction

Stacked Home Use With Lithium Ion Battery Solar Energy Storage Battery System Pack Lifepo4 Container

Features of Residential Battery Storage System

- 1. Flexible, Efficient, Simple/Easy installation/With easy transportation
- 2. Good compatibility, standrad communication protocol, CAN and RS485, compatible with most popular hybrid and off-grid inverters in the market. We can also customized your own demand.
- 3. IP55 protection class, suit for outdoor and indoor installation.
- 4. Long life cycle, more than 6000 times or 10 years.
- 5. High protection measures, built-in Aerosal active fire protection module, thermal runaway detection and active fire protection.
- 6. Quick installation design, plug and play assembly, no more cables between packs, saves manual installation costs.
- 7. The generation upgraded version, plug and play assembly, saves manual installation costs.

Steps for usage

1. Equipped with card swiping start and bluetooth remote stop and start, equipped with rechargeable IC card.


2. Scheduled charging function, which can be charged regularly according to user needs, and it will end automatically when fully charged.

3. Equipped with a display screen, real-time display of SOC information and estimated fully charging time.

Specification of Residential Battery Storage System

Model	3 modules	4 modules	5 modules	6 modules	
Nominal capacity (kwh)	7.68	10.24	12.8	15.36	
Battery cell configuration	48S1P	64S1P	80S1P	96S1P	
Operating voltage range(V)	136.8-172.8	182.4-230.4	228-288	237.6-3456	
Weight	115kg	145kg	175kg	205kg	
Nominal voltage	153.6V	204.8V	156V	307.2V	
Dimension (mm)	550x430x697.5	550x430x826.5	550x430x955.5	550x430x1084 .5	
Battery cell type	LiFePO4				
Rated working current	50A				
Communication method	CAN/RS485/RS232				
Operating temperature range	Charging: 0~45 Discharging: -10~50				
Protection level	IP55				
Installation method	Floor installation				
Cycle life	>6000 Cycles(80%DOD)				
Peak charge/discharge current	63A, (@25 ,5S)				
Self-discharge rate	≤3.5%/month/@25°C				
Series function	3S~8S				

Residential Battery Storage System Connection Diagram



FAQ

1. Is the battery used in the battery pack grade A?

for more products please visit us on esslithiumbattery.com

Yes, we only use Grade A and Brand new cells inside.

2.Do you test and match the battery before installing the battery pack? Yes, every cell will be tested capacity, IR, voltage to surely match Voltage:The deviation less than 0.01VResistance:The deviation less than $0.1m\Omega$ Capacity: Same capacity matched

3. How do I store my batteries?

When the product is not in use for a long time, it should be stored in a dry, clean and well-ventilated warehouse at 10°C 35°C, avoiding inflammable and explosive materials; the battery pack should be charged and maintained regularly every three months to ensure that the battery best performance state.

4.What is the cycle life of the battery? 6000 cycle life @ 80% DOD

5.What's the warranty of your 48V/51.2V battery pack? 5 years warranty, if there is broken item under quality problem within warranty time, we will offer free replacements or refund, up to your needs

6.Do your batteries support series or parallel connection? Our 48V battery packs support up to 15pcs in parallel, if you need series connection, please contact our sales staff



XWELL GUANGDONG XWELL TECHNOLOGY CO., LTD.

sales@esslithiumbattery.com

esslithiumbattery.com

Room 322, Building 3, No. 801, Qiaoxing Avenue, Xiaoluo Village, Shatou Street, Panyu District, Guangzhou,

+86 18620492985